

Wall2Floor Sand

Selected quartz sand, 0.3-0.9 mm.

DESCRIPTION OF THE PRODUCT

Wall2Floor Sand is a specific powder additive for the "Wall2Floor System".

APPLICATIONS

To be used exclusively in addition to **Wall2Floor Block A+B**.

IDENTIFICATION FEATURES

Selected quartz sand, 0.3-0.9 mm.

PREPARATION OF THE SUBSTRATE

Refer to the "Wall2Floor System" technical sheet.

APPLICATION

Refer to the "Wall2Floor System" technical sheet.

PREPARING THE MIXTURE

Add to **Wall2Floor Block A+B**, before application, following the methods described below and stated in the "Wall2Floor System" technical sheet.

The addition of **Wall2Floor Sand** to **Wall2Floor Block A+B** must be gradual and must always take place with mechanical mixing using a drill fitted with a whisk for approx. three minutes or until the components have been mixed completely.
Lifespan of the mixture: approx. 60 minutes.

DILUTION

It cannot be diluted

CLEANING EQUIPMENT

With nitro-thinner.

COLOURS

Colourless.

PACKAGING

55 Kg packets.

STORAGE CONDITIONS AND SHELF LIFE

If preserved in its original packaging and as long as it is kept in a covered warehouse at a temperature between +10° C and +30°C, the material has duration of 24 months.
Avoid humid storage places and protect from water, in order to prevent deterioration of the material.

N.B. - COLORIFICIO NOVACOLOR guarantees that the information herein is provided to the best of its experience and its technical and scientific knowledge; however, it cannot assume any liability for the results obtained using these products since the conditions of application are beyond its control. We recommend that you always check the suitability of the product to each specific use. This current edition supersedes all previous information sheets.