

Dune Extrawhite

Decorative architectural trowel-on coating for interiors, extra white colour

PRODUCT DESCRIPTION

Dune Extrawhite is a decorative coating for interiors with soft metallic charges that creates high-end visual effects and a stunning game of light and shades.

USES

Dune Extrawhite creates velvet-like chromatic effects that are perfectly matching the modern concept of high-end decoration of interior walls in modern environments.

IDENTIFICATION FEATURES

Binder nature: water-based acrylic polymer
Density: **Dune Extrawhite**: 1,14 +/- 0,05 g/ml

PERFORMANCES

The application of **Dune Extrawhite** is simple and practical and allows to easily achieving high quality visual and tactile effects to both, professional applicator and private unprofessional customers.

Due to its high versatility, **Dune Extrawhite** can be applied using different tools and permits to achieve many different shades, textures and customized effects.

DILUTION

Dune Extrawhite: ready to use.

WARNING

Properly mix the product before the application.

Do not apply on fresh surfaces; wait for the adequate maturation time, generally of 4 weeks.

In case of highly stressed substrates it is recommended to apply one or more coats of **Clear Coat** (clear protection for interiors), properly diluted.

SUBSTRATE PREPARATION AND APPLICATION

(Referred to environmental conditions T=25°C, UR=60%)

The substrate must be perfectly dry, dust-free, with no humidity and salt stains.

Resurface or consolidate the surface with specific products if necessary.

In case of mould, treat the surface with suitable specific products. Brush or remove any efflorescence and old peeling paint.

Higher layers of old lime-based paint and tempera paint must be removed.

Brush out dust, smog or other deposits before the application.

In case of non-homogeneous or chalky surfaces, apply one layer of **Decofix** (micronized wall sealer) diluted, with a brush.

Over dry and compact substrates, apply one layer of **Novaprimer** (water-based acrylic pigmented primer), diluted, with a brush or with a roller.

Over dry primer, apply one layer of **Dune Extrawhite** with a roller or with a trowel, spreading the paint evenly. Remove any exceeding amounts of product.

Once the surface is completely dry, apply a second layer of **Dune Extrawhite**, not diluted, with a stainless steel trowel or with a short hair roller using a bit more material.

Work into the surface still wet using a stainless steel trowel with circular movements, working the product until reaching the desired effect.

Drying time: 24 hours approx. depending on the kind of substrate, absorption rate and environmental conditions.

RECOMMENDATIONS

During the entire application process, the product must be protected from cold and high heat changes.

Do not apply with air, substrate and product temperature lower than +5°C and higher than +35°C, nor under direct sun light, nor on superheated surfaces (even if already in shadow). Environmental humidity must be <75%; substrate humidity must be <10%.

It is advisable to complete each work with materials from the same batch of production. When using multiple batches, it is recommended to remix the various products together to avoid slight differences in shading.

For the correct use, dilution and application of the products here mentioned, consult their respective technical data sheets.

During the preparation of the substrate and application of the products, it is recommended the correct use of tools and individual protective devices (dpi).

TOOLS CLEANING

With water, immediately after use.

YIELD

Dune Extrawhite: 8-10 m²/l, in two layers, depending on the kind of substrate and its absorption rate.

COLOURS

Extrawhite, **Dune** colour collection.

PACKAGES

1 l and 3 l.

SHELF LIFE

The packaged product is guaranteed for 24 months, if stored in the original sealed packages and at the adequate temperatures.

SECURITY PROCEDURES

EU Directive 2004/42/CE:

Dune Extrawhite (decorative effect coating)

UE limit value for **Dune Extrawhite** (cat A/l): 200 g/l (2010)

Dune Extrawhite contains a maximum of 200 g/l of VOC.

The product does not require labeling in accordance with the regulations in force. Use the product according to current standards of hygiene and safety. Do not empty into drains, water courses or onto the ground; after use do not litter containers, allow the residue to dry and treat them as special waste. Keep out from children presence. If swallowed, seek medical advice immediately and show this container or label.

For more information see the safety data sheet.

Technical Data Sheet: **Dune Extrawhite**

Revision n: 01

Date: 28-11-2017

Page 1 / 2

N.B.- NOVACOLOR guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets.